From	To					f((
C.O. No	0	Date				53 Te Pl	ic coil service 31 Water Street • Box 2 emple, PA 19560 hone: 610.921.3191 • ' xx: 610.929.7824 • ww	237 Toll free 1.800.523.8179	
1	HPRPM	PH	CY Volts	Serial nu	mber				
MER)	Squirrel cage Slip I	Ring Amps_	Model	Manufact	urer's name _		Frame _		
USTO	Duty - Continuous 🔲 1	Intermittent	Hours - temperature rise _	°C	Open	TEFC Totally	enclosed	Splash proof	
PLE	EASE ENTER OUR ORDER FOR	THE FOLLOWING COIL	S:						
THIS INFORMATION TO BE SUPPLIED BY CUSTOMER A PARTICULAR AND THE PROPERTY OF T	c	D STATOR BORE DIAMETER		F F G G G ER PLATE ND HEAD	CLEARANCE H H DROP	OD COIL END J ID COIL EN	M	SLOT DECIMAL DIMENSION L N N	
T) —	ORIGINAL WINDING DATA					FURNISH IN LIEU OF SAMPLE COIL			
No. of slo	ots	0	Conductor size		R	I I	J		
Stator connecti	No. circuits Y No. circuits — No. circuits		Turns per coilWo	und flat on edge		V	W X	X Y Y BOTTOM LEAD	
Conduct	tor size		No. of wires in				_\/	TOP	
Process	- Tin: Yes No]	•						
Phase	_		Weight/set						
Coil lead	ds		Coil conductor arrangement	Wide Deep			TABLE TOP		
Series									
	LEFT HAND	CLE COIL TY	RIGHT HAND	Α		STANDARD — SEALE H		Li	
5	A		- B	В		_ I			
				C		_			
}//				D					
				E			Y		
	* CHi	ECK LEAD CONNECTIO	N	F		M	Z		
	OH	OONEONO		G		N		© 2013 Electric Coil Service, inc 4.9 F5-0	